

VSR-150 Series Pressure Regulators *by American Torch Tip*

SPECS

Applications and Uses

Light Duty
Welding & Cutting Applications
Single Stage Regulator

Dimensions

4¾" w x 4¼" h x 3¼" d
(12cm x 11cm x 8cm)

Weight

1lb. 12oz. (.87kg)

Construction and Design

Brass body and housing cap, inlet, side and rear entry
1 1/2" Gauges
1 1/4" Diaphragm – reinforced neoprene
High Pressure Relief Valve – internal self-reseating

100% Tested

All American Torch Tip oxy-fuel products are leak and performance tested.



VSR-150-540



VSR-160-510

Part Number	Gas Service	Max Inlet Pressure PSIG	Delivery Range PSIG	Delivery Gauge PSIG	Supply Gauge PSIG	Inlet Connection
VSR-150R-540	Oxygen	3000	5-100	0-100	0-4000	CGA 540 rear entry inlet
VSR-150-540	Oxygen	3000	5-100	0-100	0-4000	CGA 540 side entry inlet
VSR-160R-510	Acetylene	3000	2-15	0-30	0-400	CGA 510 rear entry inlet
VSR-160-300	Acetylene	3000	2-15	0-30	0-400	CGA 510 side entry inlet
VSR-261R-510	LP/Natural Gas / Propylene	3000	2-40	0-60	0-400	CGA 510 rear entry inlet
VSR-261-510	LP/Natural Gas / Propylene	3000	2-40	0-60	0-400	CGA-510 side entry inlet

NOTE: Regulators will deliver at least the stated upper range at no flow and in some cases may exceed the stated upper range.