

ARGON/CO₂
Regulator/Flowmeter



FEATURES

- Single-stage design
- Sintered inlet filter – bronze
- Calibrated in dual-scale Argon and CO₂
- Removable outlet adapter

PRESSURES

- Outlet pressure preset: 50 PSIG
- Maximum inlet pressure: 3000 PSIG

100% TESTED

- All American Torch Tip oxy-fuel products are leak and performance tested.
- 3-Year warranty



ARGON/CO₂ Regulator/Flowmeter

SPECS

APPLICATION AND USES

Light duty
For pure or mixed gases
For MIG or TIG CO₂ shielding gases

BUILT TO LAST

Impact-resistant polycarbonate tube
All-brass construction

DIMENSIONS

5" W x 6 1/2" H x 2 1/2" D
(12.70cm x 16.51cm x 6.35cm)

WEIGHT

1lb. 8oz. (0.81 kg)

WITH HOSE

Part Number	Hose Length	Gas Service	Flow Rate	Delivery Range	Inlet Connection
AFM-100-580-CS6	6' Hose	Argon	3000	0-70	CGA 580
AFM-100-580-CS10	10' Hose	Argon	3000	0-70	CGA 580
CFM-100-320-CS6	6' Hose	CO ₂	3000	0-70	CGA 320
CFM-100-320-CS10	10' Hose	CO ₂	3000	0-70	CGA 320

WITHOUT HOSE

Part Number	Gas Service	Flow Rate	Delivery Range	Inlet Connection
AFM-100-580	Argon	3000	0-70	CGA 580
CFM-100-320	CO ₂	3000	0-70	CGA 320

NOTE: Regulators will deliver at least the stated upper range at no flow and in some cases may exceed the stated upper range.