

CUT CHARTS

OXY-FUEL Compatible with Oxweld®

1427 Alternate fuels operating data.

Steel Thickness	Tip Size	Cutting Oxygen (PSIG)	Preheat Oxygen (PSIG)*	Natural Gas (PSIG)	Cutting Speed I.P.M.	Cleaning Drill Size Gas Consumption cfh			l cfh	
						Preheat	Cutting	Cutting Oxygen	Preheat Oxygen	Natural Gas
12"	12	75-85	8-10	16-19	4-5	55	31	800-900	100-115	65-75
14"	14	60-70	7-9	8-11	3 1/2-4 41/2	54	28	950-1,100	115-140	75-95
16	16	55-65	9-12	11-15	3-4 41/2	53	20	1,150-1,330	145-175	95-115
20"	20	45-55	13-18	17-23	2 1/4	52	8	1,450-1,700	170-225	125-150
24"	24	40-50	21-25	28-33	2-3 1/2	51	С	1,850-2,200	225-285	170-190
28"	28	30-40	28-33	39-45	2-3 1/2	50	К	1,950-2,400	315-350	210-235

1427 Series Tips: Cutting speeds are based on cutting steel at room temperature and have straight cylindrical cutting bores.



† American Torch Tip Company is in no way affiliated with the above-named manufacturer(s). References to the above-named machines, torches and numbers are for your convenience only. American Torch Tip is not necessarily authorized by the above-named manufacturer(s) to provide replacement parts. Most parts advertised for sale are made by, or for, American Torch Tip Company and other parts, as indicated, are original parts manufactured by the above-named OEM and are simply being resold by American Torch Tip Company. Part numbers followed by an * are manufactured by the respective OEM.